

Historical Specification

To find historical specifications for discontinued equipment, select the product category, model number and first year of production. For additional information, visit the [service and maintenance](#) section or contact your [local dealer](#).

Family: **Compact Excavators** Model: **Bobcat 324** First year of production: **2010**

Standard Optional Not Applicable Units US

	Bobcat 324
Engine	
Emissions Tier (EPA)	Tier 4
Engine Fuel	Diesel
Maximum Governed RPM	2,500 rpm
Horsepower	13.9 hp
Turbocharged Engine	
Optional Horsepower	n/a

Performance	
Operating Weight	3,571 lb
Weight Class	1.5 t
Travel Speed - High	2.5 mph
Travel Speed - Low	1.5 mph
Arm Digging Force	1,778 lbf
Bucket Digging Force	3,620 lbf
Rated Lift Capacity	1032 lb
Lift Radius	118 in
Boom Swing - Left	80°
Boom Swing - Right	60°
Maximum Dig Depth	8.5 ft
Max Dump Height	8.7 ft
Maximum Reach at Ground Level	14 ft

Capacities

Fuel Tank	6.3 gal
-----------	---------

Hydraulic System

Auxiliary Std Flow	7.9 gal/min
--------------------	-------------

Auxiliary Pressure	3,350 psi
--------------------	-----------

Dimension

Length	153.7 in
--------	----------

Overall Length in Travel Position	153.7 in
-----------------------------------	----------

Width	38.6 in
-------	---------

Height	85.5 in
--------	---------

Height with Operator Cab	85.5 in
--------------------------	---------

Features

Air Conditioning

Cab Enclosure

Cab Heater

Heater Air Conditioning

Radio

Tail Swing Type	Conventional
-----------------	--------------

Engine Shutdown

Auxiliary Hydraulics

Secondary Auxiliary Hydraulics

Quick Tach System

Rubber Track

Angle Blade

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.